



GRIP-ESZ4





Item number 66.9446-*

For fast and safe contacting to M4 threaded bolts, for example on motor connections (contact depth 3 to 6 mm). Ø 4 mm rigid socket in handle accepting spring-loaded Ø 4 mm plugs with rigid insulating sleeve. Thread inserts are replaceable and available separately. The current depends on the thread insert.

Technical data	
Diameter of plug system	4 mm
Rated Values	1000 V, CAT IV, 20 A
Surface treatment electrical contact	Ag
Standard color(s) *	21
User-Information	I 112
Remarks	Thread insert M4 included.
Approvals	CE

GRIP-ESZ5





Item number 66.9447-*

For fast and safe contacting to M5 threaded bolts, for example on motor connections (contact depth 3 to 6 mm). Ø 4 mm rigid socket in handle accepting spring-loaded Ø 4 mm plugs with rigid insulating sleeve. Thread inserts are replaceable and available separately. The current depends on the thread insert.

Technical data	
Diameter of plug system	4 mm
Rated Values	1000 V, CAT IV, 30 A
Surface treatment electrical contact	Ag
Standard color(s) *	21
Test accessory acc. to	IEC EN 61010-031
User-Information	I 112
Remarks	Thread insert M5 included.
Approvals	CE

GRIP-ESZ6



Item number 66.9448-*

For fast and safe contacting to M6 threaded bolts, for example on motor connections (contact depth 3 to 6 mm). Ø 4 mm rigid socket in handle accepting spring-loaded Ø 4 mm plugs with rigid insulating sleeve. Thread inserts are replaceable and available separately. The current depends on the thread insert.

Technical data	
Diameter of plug system	4 mm
Rated Values	1000 V, CAT IV, 32 A
Surface treatment electrical contact	Ag
Standard color(s) *	21
Test accessory acc. to	IEC EN 61010-031
User-Information	I 112
Remarks	Thread insert M6 included.
Approvals	CE